



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 16 MM<sup>2</sup>; LATERAL MARKER SLOTS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®, 16,00 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 76; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;

Fine-stranded conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;

Strip length: 16 ... 17 mm / 0.63 ... 0.67 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 12 mm / 0.472 inch;

Inaltime from upper-edge of DIN-rail: 37,5 mm / 1.476 inch;

Adancime: 80 mm / 3.15 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,467; MJ

Greutate: 31,8; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4050821413134;  
Customs tariff number: 85369010000;  
Pret: 18,09 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-16-mm2-lateral-marker-slots-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-16-00-mm2-gray-140468>