



WAGO 1-CONDUCTOR N-DISCONNECT TERMINAL BLOCK; 6 MM²; PUSH-IN CAGE CLAMP®; 6,00 MM²; BLUE

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 51; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 2,5 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 10 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar total de conexiuni: 1;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 7,5 mm / 0.295 inch;

Inaltime from upper-edge of DIN-rail: 38,1 mm / 1.5 inch;

Adancime: 60 mm / 2.362 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,226; MJ
Greutate: 14,6; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4044918989855;
Customs tariff number: 85365080900;
Pret: 20,30 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/1-conductor-n-disconnect-terminal-block-6-mm2-push-in-cage-clamp-6-00-mm2-blue-140521>