



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR AUTOMOTIVE BLADE-
STYLE FUSES; WITH TEST OPTION; WITH BLOWN FUSE INDICATION BY LED; 12
V; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM²; CAGE CLAMP®; 6,00 MM²; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 25; A

Curent nominal 2: 30; A

Operation status indicator: 12 V;

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Fine-stranded conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 8 mm / 0.315 inch;

Inaltime from upper-edge of DIN-rail: 33,5 mm / 1.319 inch;

Adancime: 85 mm / 3.346 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Greutate: 17,9; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4055143260749;

Customs tariff number: 85369095990;

Pret: 58,70 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-fuse-terminal-block-for-automotive-blade-style-fuses-with-test-option-with-blown-fuse-indication-by-led-12-v-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-cage-clamp-6-00-mm2-gray-140553>