



**WAGO 4-CONDUCTOR FUSE TERMINAL BLOCK; WITH PIVOTING FUSE HOLDER;  
AND END PLATE; FOR 5 X 20 MM MINIATURE METRIC FUSE; WITHOUT BLOWN  
FUSE INDICATION; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM<sup>2</sup>; PUSH-IN CAGE  
CLAMP®; 2,50 MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-3;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 6,3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 250; V

Curent nominal UL (Use Group B): 6,3; A

Tensiune nominala UL (Use Group C): 250; V

Curent nominal UL (Use Group C): 6,3; A

Tensiune nominala UL (Use Group D): 250; V

Curent nominal UL (Use Group D): 6,3; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 6,3; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 6,3; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Number of jumper slots: 2;  
Latime: 6,2 mm / 0.244 inch;  
Inaltime from upper-edge of DIN-rail: 57,2 mm / 2.252 inch;  
Adancime: 87,5 mm / 3.445 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,341; MJ  
Greutate: 16,1; g  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4045454974763;  
Customs tariff number: 85369095990;  
Pret: 31,47 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-fuse-terminal-block-with-pivoting-fuse-holder-and-end-plate-for-5-x-20-mm-miniature-metric-fuse-without-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-140603>