



**WAGO TAP-OFF MODULE; FOR FLAT CABLE; 5 X 2.5 MM<sup>2</sup> + 2 X 1.5 MM<sup>2</sup>; 3-POLE;  
COD. A; WITH CABLE CONNECTION ON THE OUTPUT SIDE; BLACK**

Note on Contact Resistance: approx. 1 m $\Omega$  of contact resistance approx. 0.25 m $\Omega$  contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: IDC;

Tip actionare: Operating tool;

Numar poli: 3;

Total number of potentials: 3;

Latime: 49 mm / 1.929 inch;

Inaltime: 46,5 mm / 1.831 inch;

Adancime: 79 mm / 3.11 inch;

Coding: A;

Mating force of a plug-in connection: approx. 30 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ?200, without resistive load 100, with resistive load  $I_N = 25$  A, tested (4 mm<sup>2</sup>/12 AWG);

Marking: L ? N;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily accessible areas).;

Potential marking: L ? N;

Application: General mains applications;

Suitable: for flat cable 5 x 2.5 mm<sup>2</sup>, 5 x 4 mm<sup>2</sup>, 5 x 2.5 mm<sup>2</sup> + 2 x 1.5 mm<sup>2</sup>;

Mismatching protection: Yes;

Locking of plug-in connection: locking lever;

Culoare: black;

Material izolator: Polyamide 66 (PA 66);

Contact material: Copper or copper alloy (surface-treated);

Fire load: 1,843; MJ

Greutate: 70,1; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: PVC cable for temperatures ? 70 °C (including halogen-free)

PVC flat cable for temperatures -15 °C to ? 70 °C (including halogen-free) Insulating parts for temperatures ? 105 °C;

Product Group: 20 (WINSTA);

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4045454062019;

Customs tariff number: 85366990990;

Pret: 67,90 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tap-off-module-for-flat-cable-5-x-2-5-mm2-2-x-1-5-mm2-3-pole-cod-a-with-cable-connection-on-the-output-side-black-140608>