



**WAGO PCB TERMINAL BLOCK; 2.5 MM²; PIN SPACING 5 MM; 3-POLE; 2,50 MM²;
GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/2): 250; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Tehnologie conexiune: Screw-type connection;

Tip actionare: Operating tool;

Solid conductor: 0,5 ... 2,5 mm² / 20 ... 14 AWG;

Fine-stranded conductor: 0,5 ... 2,5 mm² / 20 ... 14 AWG;

Strip length: 5 ... 7 mm / 0.2 ... 0.28 inch;

Conductor connection direction to PCB: 0; °

Numar poli: 3;

Numar total de conexiuni: 3;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 5/5,08 mm / 0.197/0.2 inch;

Latime: 5 mm / 0.197 inch;

Inaltime de la fata: 11 mm / 0.433 inch;

Adancime: 9 mm / 0.354 inch;

PCB contact: THT;

Solder pin arrangement: over the entire terminal strip (in-line);

Number of solder pins per potential: 1;

Culoare: gray;

Material group: I;

Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 2,9; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: BOX;
Tara de origine: IN;
GTIN: 4045454539788;
Customs tariff number: 85369010000;
Pret: 5,01 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/pcb-terminal-block-2-5-mm2-pin-spacing-5-mm-3-pole-2-50-mm2-gray-140612>