



WAGO 2-CONDUCTOR MINIATURE THROUGH TERMINAL BLOCK; 2.5 MM²; WITH TEST OPTION; SUITABLE FOR EX E II APPLICATIONS; CENTER MARKING; FOR DIN-15 RAIL; CAGE CLAMP®; 2,50 MM²; LIGHT GRAY

Tensiune nominala EN (Ex e II): 690; V
Curent nominal (Ex e II): 23; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,5 ... 2,5 mm² / 20 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): 12 AWG: THHN, THWN;
Latime: 6 mm / 0.236 inch;
Inaltime from upper-edge of DIN-rail: 24,5 mm / 0.965 inch;
Adancime: 32 mm / 1.26 inch;
Design: horizontal;
Tip montaj: DIN-15 rail;
Marking level: Center marking;
Culoare: light gray;
Fire load: 0,072; MJ
Greutate: 3,8; g
Product Group: 9 (Std. Chassis Mt. Blocks);
Tip ambalare: BOX;
Tara de origine: CH;

GTIN: 4044918415019;
Customs tariff number: 85369010000;
Pret: 4,66 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-miniature-through-terminal-block-2-5-mm2-with-test-option-suitable-for-ex-e-ii-applications-center-marking-for-din-15-rail-cage-clamp-2-50-mm2-light-gray-140721>