



**WAGO 4-CONDUCTOR THROUGH TERMINAL BLOCK; 4 MM<sup>2</sup>; FOR EX E II AND EX I APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 4,00 MM<sup>2</sup>; BLUE**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 32; A

Curent nominal 2: 41; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 30; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 30; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 30; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 30; A

Tensiune nominala EN (Ex e II): 550; V

Curent nominal (Ex e II): 30; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm<sup>2</sup>;

Solid conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;

Solid conductor; push-in termination: 1,5 ... 6 mm<sup>2</sup> / 14 ... 10 AWG;

Fine-stranded conductor: 0,5 ... 6 mm<sup>2</sup> / 20 ... 10 AWG;

Fine-stranded conductor; with insulated ferrule: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1,5 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;  
Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;  
Number of jumper slots: 2;  
Latime: 6,2 mm / 0.244 inch;  
Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;  
Adancime: 78,7 mm / 3.098 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,181; MJ  
Greutate: 10,6; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4017332071826;  
Customs tariff number: 85369010000;  
Pret: 9,50 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/4-conductor-through-terminal-block-4-mm2-for-ex-e-ii-and-ex-i-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-4-00-mm2-blue-140724>