



WAGO 2-CONDUCTOR DISCONNECT/TEST TERMINAL BLOCK; E.G., VOLTAGE TRANSFORMER CIRCUITS; WITH TOUCH-PROOF TEST SOCKETS; FOR 4 MM Ø TEST PLUGS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM²; PUSH-IN CAGE CLAMP®; 6,00 MM²; GRAY

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 30; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 30; A

Tensiune nominala UL (Use Group C): 300; V

Curent nominal UL (Use Group C): 30; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 30; A

Tensiune nominala CSA (Use Group C): 300; V

Curent nominal CSA (Use Group C): 30; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 1 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with uninsulated ferrule: 1,5 ... 6 mm² / 16 ... 10 AWG;
Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 19 AWG;
Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;
Numar total de conexiuni: 2;
Total number of potentials: 2;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Number of jumper slots: 2;
Latime: 8 mm / 0.315 inch;
Inaltime from upper-edge of DIN-rail: 65,3 mm / 2.571 inch;
Adancime: 99,6 mm / 3.921 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,425; MJ
Greutate: 28; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4055143074797;
Customs tariff number: 85365080900;
Pret: 42,82 LEI (TVA inclus)

Detalii online: [https://www.materialelectrice.ro/2-conductor-disconnect-test-terminal-block-e-g-voltage-transformer-circuits-with-touch-proof-test-sockets-for-4-mm-oe-test-plugs-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-push-in-cage-clamp-6-00-mm2-gray-140732](https://www.materialeelectrice.ro/2-conductor-disconnect-test-terminal-block-e-g-voltage-transformer-circuits-with-touch-proof-test-sockets-for-4-mm-oe-test-plugs-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-push-in-cage-clamp-6-00-mm2-gray-140732)