



Image coming soon

**WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 120 MM<sup>2</sup>; LATERAL MARKER SLOTS; ONLY FOR DIN 35 X 15 RAIL; 2.3 MM THICK; COPPER; POWER CAGE CLAMP; 120,00 MM<sup>2</sup>; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: POWER CAGE CLAMP;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Nominal cross-section: 120 mm<sup>2</sup>;

Solid conductor: 50 ... 120 mm<sup>2</sup> / 1/0 AWG ... 250 kcmil;

Stranded conductor: 50 ... 120 mm<sup>2</sup> / 1/0 AWG ... 250 kcmil;

Fine-stranded conductor: 50 ... 120 mm<sup>2</sup> / 1/0 AWG ... 250 kcmil;

Fine-stranded conductor; with insulated ferrule: 50 ... 120 mm<sup>2</sup> / 1/0 AWG ... 250 kcmil;

Fine-stranded conductor; with uninsulated ferrule: 50 ... 120 mm<sup>2</sup> / 1/0 AWG ... 250 kcmil;

Strip length: 45 ... 47 mm / 1.77 ... 1.85 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 32 mm / 1.26 inch;

Inaltime from upper-edge of DIN-rail: 116 mm / 4.567 inch;

Adancime: 132 mm / 5.197 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: green-yellow;

Material izolator: Polyamide 66 (PA 66);

Greutate: 645,4; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4055143067072;  
Customs tariff number: 85369010000;  
Pret: 409,19 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-ground-terminal-block-120-mm2-lateral-marker-slots-only-for-din-35-x-15-rail-2-3-mm-thick-copper-power-cage-clamp-120-00-mm2-green-yellow-140908>