



WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR GLASS CARTRIDGE FUSE 1/4" X 1 1/4"; WITH BLOWN FUSE INDICATION BY NEON LAMP; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM²; CAGE CLAMP®; 6,00 MM²; GRAY

Voltage type 1: AC/DC;
Tesiune nominala (III/3): 120; V
Curent nominal: 10; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;
Fine-stranded conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;
Numar total de conexiuni: 2;
Total number of potentials: 2;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 13 mm / 0.512 inch;
Inaltime from upper-edge of DIN-rail: 56,5 mm / 2.224 inch;
Adancime: 62 mm / 2.441 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Side marking;
Culoare: gray;
Greutate: 27,2; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: CN;

GTIN: 4050821110347;
Customs tariff number: 85369095990;
Pret: 64,79 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-fuse-terminal-block-for-glass-cartridge-fuse-x-1-with-blown-fuse-indication-by-neon-lamp-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-cage-clamp-6-00-mm2-gray-140914>