



**WAGO FEMALE CONNECTOR; WITH DIRECT GROUND CONTACT; 3-POLE; 1,00  
MM<sup>2</sup>; WHITE**

Tensiune nominala (III/2): 500; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Curent nominal: 6; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Tehnologie conexiune: PUSH WIRE®;  
Strip length: 8 mm / 0.31 inch;  
Numar poli: 3;  
Numar tipuri de conexiuni: 1;  
Latime: 26 mm / 1.024 inch;  
Inaltime de la fata: 34 mm / 1.339 inch;  
Adancime: 42 mm / 1.654 inch;  
Culoare: white;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,146; MJ  
Greutate: 7,1; g  
Temperature stability: 105; °C  
Product Group: 8 (Misc. Chassis Mount Blocks);  
Tip ambalare: bag;  
Tara de origine: PL;  
GTIN: 4044918499736;

Customs tariff number: 85369010000;  
Pret: 14,87 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/female-connector-with-direct-ground-contact-3-pole-1-00-mm2-white-140953>