



**WAGO SMD PCB TERMINAL BLOCK; PUSH-BUTTON; 1.5 MM²; PIN SPACING 6 MM;
3-POLE; PUSH-IN CAGE CLAMP®; IN TAPE-AND-REEL PACKAGING; 1,50 MM²;
WHITE**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 17,5; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-button;

Solid conductor: 0.5 ... 1.5 mm² / 20 ... 16 AWG;

Fine-stranded conductor: 0.5 ... 1.5 mm² / 20 ... 16 AWG;

Fine-stranded conductor; with insulated ferrule: 0.5 ... 0.75 mm²;

Fine-stranded conductor; with uninsulated ferrule: 0.5 ... 0.75 mm²;

Strip length: 7 ... 10 mm / 0.28 ... 0.39 inch;

Conductor connection direction to PCB: 0; °

Numar poli: 3;

Numar total de conexiuni: 3;

Total number of potentials: 3;

Numar tipuri de conexiuni: 1;
Numar nivele: 1;
Distanta intre pini: 6 mm / 0.24 inch;
Latime: 17.7 mm / 0.697 inch;
Inaltime: 5.6 mm / 0.22 inch;
Inaltime de la fata: 5.6 mm / 0.22 inch;
Adancime: 15.8 mm / 0.622 inch;
Reel diameter of tape-and-reel packaging: 330; mm
Tape Latime: 24; mm
PCB contact: SMD;
Culoare: white;
Material group: I;
Material izolator: Polyphthalamide (PPA GF);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy;
Contact plating: tin-plated;
Greutate: 1,6; g
Temperatura lucru: -60 ... +105 °C;
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4055143242783;
Customs tariff number: 85369010000;
Pret: 8,11 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/smd-pcb-terminal-block-push-button-1-5-mm2-pin-spacing-6-mm-3-pole-push-in-cage-clamp-in-tape-and-reel-packaging-1-50-mm2-white-141049>