



**WAGO COMPONENT TERMINAL BLOCK; 4-CONDUCTOR; WITH DIODE 1N5408;  
ANODE, RIGHT SIDE; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 4 MM<sup>2</sup>; CAGE CLAMP®;  
4,00 MM<sup>2</sup>; GRAY**

Tesiune nominala: 250; V  
Reverse voltage: 1.000; V  
Ratings per: IEC/EN 60947-7-1;  
Curent nominal: 1,5; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0.08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
Numar total de conexiuni: 4;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 6 mm / 0.236 inch;  
Inaltime from upper-edge of DIN-rail: 29 mm / 1.142 inch;  
Adancime: 86 mm / 3.386 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,206; MJ  
Greutate: 13,7; g  
Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4050821275527;  
Customs tariff number: 85369010000;  
Pret: 36,13 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/component-terminal-block-4-conductor-with-diode-1n5408-anode-right-side-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-141149>