



**WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM<sup>2</sup>; SUITABLE FOR EX E II APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®; 2,50 MM<sup>2</sup>; RED**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Curent nominal 2: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 20; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 20; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 20; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 20; A

Tensiune nominala EN (Ex e II): 550; V

Curent nominal (Ex e II): 22; A

Curent nominal (Ex e II) with jumper: 20; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm<sup>2</sup>;

Solid conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm<sup>2</sup> / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm<sup>2</sup> / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm<sup>2</sup> / 18 ... 12 AWG;  
Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;  
Number of jumper slots: 2;  
Latime: 5,2 mm / 0.205 inch;  
Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;  
Adancime: 59,2 mm / 2.33 inch;  
Design: horizontal;  
Tip montaj: DIN-35 rail;  
Marking level: Center/side marking;  
Culoare: red;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,104; MJ  
Greutate: 6,2; g  
Product Group: 22 (TOPJOB S);  
Tip ambalare: BOX;  
Tara de origine: DE;  
GTIN: 4044918081498;  
Customs tariff number: 85369010000;  
Pret: 5,97 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-through-terminal-block-2-5-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-2-50-mm2-red-141180>