



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; WITH PIVOTING FUSE HOLDER;  
FOR 5 X 20 MM MINIATURE METRIC FUSE; WITH BLOWN FUSE INDICATION BY  
NEON LAMP; 120 V; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 4 MM<sup>2</sup>; CAGE CLAMP®; 4,00  
MM<sup>2</sup>; GRAY**

Ratings per: IEC/EN 60947-7-3;

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 10; A

Operation status indicator: 120 V;

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 8 mm / 0.315 inch;

Inaltime from upper-edge of DIN-rail: 60 mm / 2.362 inch;

Adancime: 60 mm / 2.362 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,333; MJ  
Greutate: 17,5; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4045454871444;  
Customs tariff number: 85369095990;  
Pret: 69,69 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-fuse-terminal-block-with-pivoting-fuse-holder-for-5-x-20-mm-miniature-metric-fuse-with-blown-fuse-indication-by-neon-lamp-120-v-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-141217>