



**WAGO 2-CONDUCTOR N-DISCONNECT TERMINAL BLOCK; 2.5 MM²; PUSH-IN
CAGE CLAMP®; 2,50 MM²; BLUE**

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 5,2 mm / 0.205 inch;

Inaltime from upper-edge of DIN-rail: 38,1 mm / 1.5 inch;

Adancime: 67,3 mm / 2.65 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,173; MJ
Greutate: 10,2; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4045454802295;
Customs tariff number: 85365080900;
Pret: 17,38 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-n-disconnect-terminal-block-2-5-mm2-push-in-cage-clamp-2-50-mm2-blue-141221>