



**WAGO 2-CONDUCTOR DISCONNECT TERMINAL BLOCK; WITH TEST OPTION;
ORANGE DISCONNECT LINK; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM²; CAGE
CLAMP®; 6,00 MM²; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 30; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Fine-stranded conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 8 mm / 0.315 inch;

Inaltime from upper-edge of DIN-rail: 37 mm / 1.457 inch;

Adancime: 85 mm / 3.346 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,31; MJ

Greutate: 18,7; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821234524;
Customs tariff number: 85365080900;
Pret: 24,66 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-disconnect-terminal-block-with-test-option-orange-disconnect-link-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-cage-clamp-6-00-mm2-gray-141357>