



WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 1,5 MM²; SUITABLE FOR EX I APPLICATIONS; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 1,50 MM²; BLUE

Ratings per: IEC/EN 60947-7-1;

Tesiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 18; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 3;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 4 mm / 0.157 inch;

Inaltime from upper-edge of DIN-rail: 27 mm / 1.063 inch;

Adancime: 62,5 mm / 2.461 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: blue;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,104; MJ

Greutate: 5,4; g

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918650526;
Customs tariff number: 85369010000;
Pret: 5,91 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-through-terminal-block-1-5-mm2-suitable-for-ex-i-applications-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-1-50-mm2-blue-141520>