



WAGO MALE CONNECTOR; 7-POLE; 2,50 MM²; WHITE

Ratings per: IEC/EN 61984;

Tensiune nominala (III/2): 500; V

Tensiune nominala de supratensiune (III/2): 4; kV

Curent nominal: 16; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Certificari: UL 1059;

Connection type (1): PUSH WIRE® connection;

Tehnologie conexiune: PUSH WIRE®;

Number of connection points (connection type): 1;

Solid conductor: 1,5 ... 2,5 mm² / 16 ... 14 AWG;

Strip length: 11 ... 12 mm / 0.43 ... 0.47 inch;

Connection type 2: PUSH WIRE® connection;

Tehnologie conexiune 2: PUSH WIRE®;

Number of connection points: 1;

Solid conductor 2: 0,75 ... 1,5 mm² / 18 ... 16 AWG;

Strip length 2: 11 ... 12 mm / 0.43 ... 0.47 inch;

Numar tipuri de conexiuni: 2;

Numar nivele: 2;

Latime: 35 mm / 1.378 inch;

Inaltime de la fata: 18 mm / 0.709 inch;

Adancime: 39 mm / 1.535 inch;

Culoare: white;

Material group: I;

Material izolator: Polyamide 66 (PA 66);

Flammability class per UL94: V0;

Clamping spring material: Chrome nickel spring steel (CrNi);

Contact material: Cupru electrolitic(ECu);

Contact plating: tin-plated;
Fire load: 0,281; MJ
Greutate: 19,6; g
Temperature stability: 105; °C
Product Group: 8 (Misc. Chassis Mount Blocks);
Tip ambalare: BOX;
Tara de origine: PL;
GTIN: 4050821307914;
Customs tariff number: 85369010000;
Pret: 14,87 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/male-connector-7-pole-2-50-mm2-white-141524>