



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR CLASS CC FUSES; 2-POLE;
WITH BLOWN FUSE INDICATION; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 16 MM²;
CAGE CLAMP®; 16,00 MM²; LIGHT GRAY**

Voltage type 1: AC;
Voltage type 2: DC;
Ratings per: IEC/EN 60947-7-3;
Tensiune nominala (III/3): 600; V
Curent nominal: 32; A
Tensiune nominala (III/3) 2: 600; V
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 2,5 ... 16 mm² / 14 ... 6 AWG;
Fine-stranded conductor: 2,5 ... 16 mm² / 16 ... 6 AWG;
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;
Numar poli: 2;
Numar total de conexiuni: 4;
Total number of potentials: 2;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 35 mm / 1.378 inch;
Inaltime from upper-edge of DIN-rail: 55 mm / 2.165 inch;
Adancime: 105 mm / 4.134 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 1,1; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

GTIN: 4050821508281;

Pret: 302,95 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-fuse-terminal-block-for-class-cc-fuses-2-pole-with-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-16-mm2-cage-clamp-16-00-mm2-light-gray-141612>