



WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR GLASS CARTRIDGE FUSE 1/4" X 1 1/4"; WITH BLOWN FUSE INDICATION BY LED; 24 VDC; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM²; CAGE CLAMP®; 6,00 MM²; GRAY

Voltage type 1: DC;

Tesiune nominala (III/3): 24; V

Curent nominal: 10; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Fine-stranded conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 13 mm / 0.512 inch;

Inaltime from upper-edge of DIN-rail: 56,5 mm / 2.224 inch;

Adancime: 62 mm / 2.441 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: gray;

Greutate: 28; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4050821110323;
Customs tariff number: 85369095990;
Pret: 64,79 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-fuse-terminal-block-for-glass-cartridge-fuse-x-1-with-blown-fuse-indication-by-led-24-vdc-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-cage-clamp-6-00-mm2-gray-141653>