



**WAGO 4-CONDUCTOR THROUGH TERMINAL BLOCK; 4 MM²; WITH TEST PORT;
WITHOUT SHIELD CONTACT; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X
7.5; CAGE CLAMP®; 4,00 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;
Tesiune nominala (III/3): 800; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 20; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;
Numar total de conexiuni: 4;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 5 mm / 0.197 inch;
Inaltime from upper-edge of DIN-rail: 29 mm / 1.142 inch;
Adancime: 87 mm / 3.425 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,176; MJ
Greutate: 10,8; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: PL;

GTIN: 4044918560757;

Customs tariff number: 85369010000;

Pret: 10,75 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/4-conductor-through-terminal-block-4-mm2-with-test-port-without-shield-contact-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-4-00-mm2-gray-141686>