



**WAGO TRIPLE-DECK TERMINAL BLOCK; GROUND
CONDUCTOR/THROUGH/THROUGH TERMINAL BLOCK; PE/N/L; WITHOUT
MARKER CARRIER; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 2.5 MM²; CAGE CLAMP®;
2,50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 6;

Total number of potentials: 3;

Numar nivele: 3;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 52,5 mm / 2.067 inch;

Adancime: 106 mm / 4.173 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Potential marking: PE/N/L;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,275; MJ
Greutate: 19; g
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454129095;
Customs tariff number: 85369010000;
Pret: 30,99 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/triple-deck-terminal-block-ground-conductor-through-through-terminal-block-pe-n-l-without-marker-carrier-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-141691>