



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR CLASS CC FUSES; 1-POLE;  
WITHOUT BLOWN FUSE INDICATION; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 16 MM<sup>2</sup>;  
CAGE CLAMP®; 16,00 MM<sup>2</sup>; LIGHT GRAY**

Voltage type 1: AC;  
Voltage type 2: DC;  
Ratings per: IEC/EN 60947-7-3;  
Tensiune nominala (III/3): 600; V  
Curent nominal: 32; A  
Tensiune nominala (III/3) 2: 600; V  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 2,5 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;  
Fine-stranded conductor: 2,5 ... 16 mm<sup>2</sup> / 16 ... 6 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Numar poli: 1;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 17,5 mm / 0.689 inch;  
Inaltime from upper-edge of DIN-rail: 55 mm / 2.165 inch;  
Adancime: 105 mm / 4.134 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Culoare: light gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 1,1; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

GTIN: 4050821508151;

Pret: 83,25 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-fuse-terminal-block-for-class-cc-fuses-1-pole-without-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-16-mm2-cage-clamp-16-00-mm2-light-gray-141884>