



WAGO DOUBLE POTENTIAL TERMINAL BLOCK; 1.5 MM²; WITH DOUBLE, CENTER MARKER SLOT; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 1,50 MM²; GRAY

Ratings per: IEC/EN 60947-7-1;

Tesiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 18; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Fine-stranded conductor: 0,08 ... 1,5 mm² / 28 ... 16 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 4 mm / 0.157 inch;

Inaltime from upper-edge of DIN-rail: 27 mm / 1.063 inch;

Adancime: 73 mm / 2.874 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,118; MJ

Greutate: 6,1; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4050821214892;

Customs tariff number: 85369010000;

Pret: 8,96 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/double-potential-terminal-block-1-5-mm2-with-double-center-marker-slot-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-1-50-mm2-gray-142000>