



WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR CYLINDRICAL FUSES 10 X 38 MM; 13/32" X 11/2"; FOR PHOTOVOLTAIC APPLICATIONS; WITHOUT BLOWN FUSE INDICATION; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 16 MM²; CAGE CLAMP®; 16,00 MM²; LIGHT GRAY

Voltage type 1: DC;
Ratings per: IEC/EN 60947-7-3;
Tesiune nominala (III/3): 1000; V
Curent nominal: 32; A
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Operating tool;
Connectable conductor materials: Copper;
Solid conductor: 2,5 ... 16 mm² / 14 ... 6 AWG;
Fine-stranded conductor: 2,5 ... 16 mm² / 16 ... 6 AWG;
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;
Numar poli: 1;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Side-entry wiring;
Latime: 17,5 mm / 0.689 inch;
Inaltime from upper-edge of DIN-rail: 55 mm / 2.165 inch;
Adancime: 105 mm / 4.134 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Culoare: light gray;
Material izolator: Polyamide 66 (PA 66);
Greutate: 63,1; g

Tip ambalare: BOX;
Tara de origine: CN;
GTIN: 4050821849001;
Customs tariff number: 85369095990;
Pret: 65,98 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-fuse-terminal-block-for-cylindrical-fuses-10-x-38-mm-13-32-x-11-2-for-photovoltaic-applications-without-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-16-mm2-cage-clamp-16-00-mm2-light-gray-142103>