



**WAGO 2-CONDUCTOR FUSE TERMINAL BLOCK; FOR CYLINDRICAL FUSES 10 X 38 MM; 13/32" X 11/2"; FOR PHOTOVOLTAIC APPLICATIONS; WITHOUT BLOWN FUSE INDICATION; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 16 MM<sup>2</sup>; CAGE CLAMP®; 16,00 MM<sup>2</sup>; LIGHT GRAY**

Voltage type 1: DC;  
Ratings per: IEC/EN 60947-7-3;  
Tesiune nominala (III/3): 1000; V  
Curent nominal: 32; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 2,5 ... 16 mm<sup>2</sup> / 14 ... 6 AWG;  
Fine-stranded conductor: 2,5 ... 16 mm<sup>2</sup> / 16 ... 6 AWG;  
Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;  
Numar poli: 1;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Side-entry wiring;  
Latime: 17,5 mm / 0.689 inch;  
Inaltime from upper-edge of DIN-rail: 55 mm / 2.165 inch;  
Adancime: 105 mm / 4.134 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Culoare: light gray;  
Material izolator: Polyamide 66 (PA 66);  
Greutate: 63,1; g

Tip ambalare: BOX;  
Tara de origine: CN;  
GTIN: 4050821849001;  
Customs tariff number: 85369095990;  
Pret: 65,98 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-fuse-terminal-block-for-cylindrical-fuses-10-x-38-mm-13-32-x-11-2-for-photovoltaic-applications-without-blown-fuse-indication-for-din-rail-35-x-15-and-35-x-7-5-16-mm2-cage-clamp-16-00-mm2-light-gray-142103>