



**WAGO PCB TERMINAL BLOCK; 1.5 MM<sup>2</sup>; PIN SPACING 3.5 MM; 2-POLE; PUSH WIRE®; 1,50 MM<sup>2</sup>; WHITE**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Tensiune nominala (III/2): 320; V

Tensiune nominala de supratensiune (III/2): 4; kV

Tensiune nominala (II/2): 630; V

Tensiune nominala de supratensiune (II/2): 4; kV

Curent nominal: 2; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 6; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 6; A

Certificari: UL 1059;

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Operating tool;

Solid conductor: 0,5 ... 1,5 mm<sup>2</sup> / 20 ... 16 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Conductor connection direction to PCB: 0; °

Numar poli: 2;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 3,5 mm / 0.138 inch;

Latime: 7,9 mm / 0.311 inch;

Inaltime: 9 mm / 0.354 inch;  
Inaltime de la fata: 6,6 mm / 0.26 inch;  
Adancime: 12,5 mm / 0.492 inch;  
Lungimea pinului de contact: 2,4; mm  
Solder pin dimensions: 0,35 x 0,9 mm;  
Diametrul de gaurire cu toleranta: 1,1 (-0,1) mm;  
Twist protection: Additional anti-rotating pin;  
PCB contact: THT;  
Solder pin arrangement: over the entire terminal strip (staggered);  
Number of solder pins per potential: 1;  
Culoare: white;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Copper alloy;  
Contact plating: tin-plated;  
Greutate: 0,6; g  
Temperatura lucru: -60 ... +105 °C;  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4055143812740;  
Pret: 2,57 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/pcb-terminal-block-1-5-mm2-pin-spacing-3-5-mm-2-pole-push-wire-1-50-mm2-white-142163>