



**WAGO 2-CONDUCTOR DISCONNECT/TEST TERMINAL BLOCK; WITH TEST
OPTION; FOR 4 MM Ø TEST PLUGS; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; 6 MM²;
CAGE CLAMP®; 6,00 MM²; GRAY**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 41; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Fine-stranded conductor: 0,2 ... 6 mm² / 24 ... 10 AWG;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 8 mm / 0.315 inch;

Inaltime from upper-edge of DIN-rail: 37 mm / 1.457 inch;

Adancime: 87,5 mm / 3.445 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Marking level: Side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Greutate: 22,7; g

Product Group: 1 (Rail Mounted Terminal Blocks);

Tip ambalare: BOX;

Tara de origine: CN;
GTIN: 4045454448455;
Customs tariff number: 85369010000;
Pret: 36,01 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-disconnect-test-terminal-block-with-test-option-for-4-mm-oe-test-plugs-for-din-rail-35-x-15-and-35-x-7-5-6-mm2-cage-clamp-6-00-mm2-gray-142209>