



**WAGO 1-CONDUCTOR/1-PIN DOUBLE DECK RECEPTACLE TERMINAL BLOCK;
GROUND CONDUCTOR/THROUGH TERMINAL BLOCK; PE/L; FOR DIN-RAIL 35 X 15
AND 35 X 7.5; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 16; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm² / 28 ... 12 AWG;

Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 40 mm / 1.575 inch;

Adancime: 70 mm / 2.756 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Potential marking: PE/L;

Marking level: Side marking;

Culoare: gray;

Fire load: 0,163; MJ

Greutate: 10,6; g

Tip ambalare: BOX;

Tara de origine: DE;
GTIN: 4045454225360;
Customs tariff number: 85369010000;
Pret: 15,17 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/1-conductor-1-pin-double-deck-receptacle-terminal-block-ground-conductor-through-terminal-block-pe-l-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-cage-clamp-2-50-mm2-gray-142235>