



WAGO 2-CONDUCTOR MINIATURE THROUGH TERMINAL BLOCK; 2.5 MM²; WITH TEST OPTION; SUITABLE FOR EX I APPLICATIONS; CENTER MARKING; FOR DIN-15 RAIL; CAGE CLAMP®; 2,50 MM²; BLUE

Tensiune nominala (III/3): 800; V

Tensiune nominala de supratensiune (III/3): 8; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 6 mm / 0.236 inch;

Inaltime from upper-edge of DIN-rail: 24,5 mm / 0.965 inch;

Adancime: 32 mm / 1.26 inch;

Design: horizontal type;

Tip montaj: DIN-15 rail;

Marking level: Center marking;

Culoare: blue;

Fire load: 0,071; MJ

Greutate: 3,7; g

Product Group: 9 (Std. Chassis Mt. Blocks);

Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4044918415378;
Customs tariff number: 85369010000;
Pret: 4,84 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-miniature-through-terminal-block-2-5-mm2-with-test-option-suitable-for-ex-i-applications-center-marking-for-din-15-rail-cage-clamp-2-50-mm2-blue-142279>