



**WAGO 2-CONDUCTOR GROUND TERMINAL BLOCK; 4 MM²; WITH TEST PORT;
SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE
CLAMP®; 4,00 MM²; GREEN-YELLOW**

Ratings per: IEC/EN 60947-7-2;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Push-button;

Connectable conductor materials: Copper;

Nominal cross-section: 4 mm²;

Solid conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Solid conductor; push-in termination: 1 ... 6 mm² / 14 ... 10 AWG;

Fine-stranded conductor: 0,5 ... 6 mm² / 20 ... 10 AWG;

Fine-stranded conductor; with insulated ferrule: 1,5 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1,5 ... 4 mm² / 18 ... 12 AWG;

Strip length: 11 ... 13 mm / 0.43 ... 0.51 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross section can also be inserted via push-in termination.;

Number of jumper slots: 2;

Latime: 6,2 mm / 0.244 inch;

Inaltime from upper-edge of DIN-rail: 32,9 mm / 1.295 inch;

Adancime: 52,3 mm / 2.059 inch;

Design: horizontal;

Tip montaj: DIN-35 rail;

Marking level: Center/side marking;

Culoare: green-yellow;

Material izolator: Polyamide 66 (PA 66);

Greutate: 12,3; g

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4055143711456;

Customs tariff number: 85369010000;

Pret: 18,51 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-ground-terminal-block-4-mm2-with-test-port-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-4-00-mm2-green-yellow-142410>