



WAGO SOCKET; WITH STRAIN RELIEF HOUSING; 2-POLE; COD. E; GREEN

Note on Contact Resistance: $\approx 3m\Omega$ contact resistance

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 50; V

Tensiune nominala de supratensiune (III/3): 0,8; kV

Curent nominal: 3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: PUSH WIRE®;

Tip actionare: Push-in;

Conductor diameter: 0,8 mm;

Strip length: 9 mm / 0.35 inch;

Note (strip length): see also packaging or instructions;

Numar poli: 2;

Numar total de conexiuni: 2;

Total number of potentials: 2;

Connectable sheathed cable diameter: 5 ... 7 mm;

Conductor entry direction to mating direction: 0; °

Latime: 14,1 mm / 0.555 inch;

Adancime: 47,5 mm / 1.87 inch;

Technologie: KNX;

Coding: E;

Mating force of a plug-in connection: approx. 10 ... 15 N;

Retention force of a plug-in connection: Locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 15 ... 20 N;

Number of mating cycles: ≈ 200 ;

Marking: 1+ 2-;

Protection type: IP20;

Note on protection type: Only when mated and secured with a strain relief housing (These compact

connectors are not designed for use in open, easily accessible areas.);
Potential marking: 1+ 2-;
Application: KNX;
Tip contact (pluggable connector): Conector mama/priza;
Connector (connection type): for conductor;
Mismatching protection: Yes;
Locking of plug-in connection: locking lever;
Locking lever: retrofittable;
Strain relief: strain relief housing;
Culoare: green;
Material izolator: Polyamide 66 (PA 66);
Fire class per EN 50575: Eca;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Copper alloy (surface-treated);
Fire load: 0,15; MJ
Greutate: 5; g
Processing temperature: -5 ... +40 °C;
Continuous operating temperature: -35 ... +85 °C;
Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;
Product Group: 20 (WINSTA);
Tip ambalare: BOX;
Tara de origine: CH;
GTIN: 4045454267469;
Customs tariff number: 85366990990;
Pret: 36,19 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/socket-with-strain-relief-housing-2-pole-cod-e-green-142503>