



**WAGO 3-CONDUCTOR DISCONNECT TERMINAL BLOCK; FOR DIN-RAIL 35 X 15  
AND 35 X 7.5; 4 MM<sup>2</sup>; CAGE CLAMP®; 4,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 400; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 10; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
Numar total de conexiuni: 3;  
Total number of potentials: 2;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 6 mm / 0.236 inch;  
Inaltime from upper-edge of DIN-rail: 53,5 mm / 2.106 inch;  
Adancime: 73,5 mm / 2.894 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: gray;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,191; MJ  
Greutate: 11,5; g  
Product Group: 1 (Rail Mounted Terminal Blocks);  
Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4044918632027;  
Customs tariff number: 85365080900;  
Pret: 15,11 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-disconnect-terminal-block-for-din-rail-35-x-15-and-35-x-7-5-4-mm2-cage-clamp-4-00-mm2-gray-142542>