



WAGO FEEDTHROUGH TERMINAL BLOCK; LEVER; PLATE THICKNESS: 3 MM; 16 MM²; PIN SPACING 11.5 MM; 4-POLE; CAGE CLAMP®; 16,00 MM²; GRAY

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 8; kV

Tensiune nominala (III/2): 1000; V

Tensiune nominala de supratensiune (III/2): 8; kV

Tensiune nominala (II/2): 1000; V

Tensiune nominala de supratensiune (II/2): 8; kV

Curent nominal: 57; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 600; V

Curent nominal UL (Use Group B): 30; A

Tensiune nominala UL (Use Group C): 600; V

Curent nominal UL (Use Group C): 30; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 30; A

Tensiune nominala CSA (Use Group C): 600; V

Curent nominal CSA (Use Group C): 30; A

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Lever;

Solid conductor: 1,5 ... 16 mm² / 16 ... 6 AWG;

Fine-stranded conductor: 1,5 ... 16 mm² / 16 ... 6 AWG;

Fine-stranded conductor; with insulated ferrule: 1,5 ... 10 mm²;

Fine-stranded conductor; with uninsulated ferrule: 1,5 ... 10 mm²;

Strip length: 12 ... 13 mm / 0.47 ... 0.51 inch;

Numar poli: 4;

Numar total de conexiuni: 8;
Total number of potentials: 4;
Numar tipuri de conexiuni: 2;
Numar nivele: 1;
Distanta intre pini: 11,5 mm / 0.453 inch;
Latime: 65,1 mm / 2.563 inch;
Inaltime: 48,5 mm / 1.909 inch;
Adancime: 79,1 mm / 3.114 inch;
Housing sheet thickness: 3 ... 3 mm / 0.118 ... 0.118 inch;
Tip montaj: Locking claw;
Tip montaj: Feed-through mounting;
Culoare: gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Clamping spring material: Chrome nickel spring steel (CrNi);
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Greutate: 121,5; g
Temperatura lucru: -60 ... +105 °C;
Product Group: 4 (Printed Circuit);
Tip ambalare: bag;
Tara de origine: CN;
GTIN: 4050821148777;
Customs tariff number: 85369010000;
Pret: 125,71 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/feedthrough-terminal-block-lever-plate-thickness-3-mm-16-mm2-pin-spacing-11-5-mm-4-pole-cage-clamp-16-00-mm2-gray-142598>