



**WAGO 2-CONDUCTOR N-DISCONNECT TERMINAL BLOCK; 4 MM<sup>2</sup>; CAGE CLAMP®;**  
**4,00 MM<sup>2</sup>; BLUE**

Tensiune nominala (III/3): 400; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 32; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Open Tool Slot;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;

Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Front-entry wiring;

Latime: 6 mm / 0.236 inch;

Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;

Adancime: 77 mm / 3.031 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: blue;

Greutate: 17,8; g

Product Group: 17 (TOP JOB installation terminal blocks);

Tip ambalare: BOX;

Tara de origine: PL;

GTIN: 4044918808088;

Customs tariff number: 85365080900;  
Pret: 18,09 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-n-disconnect-terminal-block-4-mm2-cage-clamp-4-00-mm2-blue-142688>