



**WAGO DOUBLE-DECK FUSE TERMINAL BLOCK; WITH PIVOTING FUSE HOLDER;
THROUGH/FUSE TERMINAL BLOCK; FOR 5 X 20 MM MINIATURE METRIC FUSE;
WITH BLOWN FUSE INDICATION BY LED; 230 V; FOR DIN-RAIL 35 X 15 AND 35 X
7.5; 2.5 MM²; PUSH-IN CAGE CLAMP®; 2,50 MM²; GRAY**

Ratings per: IEC/EN 60947-7-3;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 6,3; A

Operation status indicator: 230 V;

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL (Use Group B): 230; V

Curent nominal UL (Use Group B): 6,3; A

Tensiune nominala UL (Use Group C): 230; V

Curent nominal UL (Use Group C): 6,3; A

Certificari: UL 1059;

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 2,5 mm²;

Solid conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Solid conductor; push-in termination: 0,75 ... 4 mm² / 18 ... 12 AWG;

Fine-stranded conductor: 0,25 ... 4 mm² / 22 ... 12 AWG;

Fine-stranded conductor; with insulated ferrule: 1 ... 2,5 mm² / 18 ... 12 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 1 ... 2,5 mm² / 18 ... 12 AWG;

Strip length: 10 ... 12 mm / 0.39 ... 0.47 inch;

Numar total de conexiuni: 4;

Total number of potentials: 2;

Numar nivele: 2;

Wiring type: Front-entry wiring;

Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;

Latime: 6,2 mm / 0.244 inch;

Inaltime from upper-edge of DIN-rail: 76,4 mm / 3.008 inch;

Adancime: 93 mm / 3.661 inch;

Design: horizontal type;

Tip montaj: DIN-35 rail;

Potential marking: L/L;

Marking level: Center/side marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Greutate: 23,2; g

Product Group: 22 (TOPJOB S);

Tip ambalare: BOX;

Tara de origine: CN;

GTIN: 4050821272090;

Customs tariff number: 85369095990;

Pret: 75,66 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/double-deck-fuse-terminal-block-with-pivoting-fuse-holder-through-fuse-terminal-block-for-5-x-20-mm-miniature-metric-fuse-with-blown-fuse-indication-by-led-230-v-for-din-rail-35-x-15-and-35-x-7-5-2-5-mm2-push-in-cage-clamp-2-50-mm2-gray-142768>