



WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 35 MM²; WITH INTEGRATED END PLATE; SUITABLE FOR EX I APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 35,00 MM²; BLUE

Ratings per: IEC/EN 60947-7-1;
Tensiune nominala (III/3): 1000; V
Tensiune nominala de supratensiune (III/3): 8; kV
Curent nominal: 125; A
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;
Tehnologie conexiune: CAGE CLAMP®;
Tip actionare: Open Tool Slot;
Connectable conductor materials: Copper;
Solid conductor: 6 ... 35 mm² / 8 ... 2 AWG;
Strip length: 23 mm / 0.91 inch;
Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Latime: 16 mm / 0.63 inch;
Inaltime from upper-edge of DIN-rail: 44,5 mm / 1.752 inch;
Adancime: 114 mm / 4.488 inch;
Design: angled;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: blue;
Material izolator: Polyamide 66 (PA 66);
Fire load: 1,103; MJ
Greutate: 87,2; g
Product Group: 17 (TOP JOB installation terminal blocks);

Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454400583;
Customs tariff number: 85369010000;
Pret: 58,76 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-35-mm2-with-integrated-end-plate-suitable-for-ex-i-applications-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-35-00-mm2-blue-142808>