



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 16 MM<sup>2</sup>; CENTER MARKING;  
FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 16,00 MM<sup>2</sup>; BLUE**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 1000; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 76; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Open Tool Slot;  
Connectable conductor materials: Copper;  
Solid conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Fine-stranded conductor: 0,2 ... 16 mm<sup>2</sup> / 24 ... 6 AWG;  
Strip length: 16 ... 17 mm / 0.63 ... 0.67 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 12 mm / 0.472 inch;  
Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;  
Adancime: 88,5 mm / 3.484 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: blue;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,489; MJ  
Greutate: 32,2; g  
Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4044918582407;  
Customs tariff number: 85369010000;  
Pret: 18,75 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-16-mm2-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-16-00-mm2-blue-142831>