



**WAGO 2-CONDUCTOR TERMINAL BLOCK; SUITABLE FOR EX I APPLICATIONS;  
WITHOUT PUSH-BUTTONS; WITH SNAP-IN MOUNTING FOOT; FOR PLATE  
THICKNESS 0.6 - 1.2 MM; FIXING HOLE 3.5 MM Ø; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50  
MM<sup>2</sup>; BLUE**

Tensiune nominala (III/3): 500; V

Tensiune nominala de supratensiune (III/3): 6; kV

Curent nominal: 24; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper;

Solid conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 14 AWG;

Fine-stranded conductor: 0.08 ... 2.5 mm<sup>2</sup> / 28 ... 14 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 2;

Total number of potentials: 1;

Numar nivele: 1;

Wiring type: Side-entry wiring;

Latime: 6 mm / 0.236 inch;

Inaltime de la fata: 18 mm / 0.709 inch;

Adancime: 28 mm / 1.102 inch;

Design: horizontal;

Tip montaj: Snap-in mounting foot;

Marking level: Side marking;

Culoare: blue;

Fire load: 0,042; MJ

Greutate: 2,3; g

Product Group: 9 (Std. Chassis Mt. Blocks);  
Tip ambalare: BOX;  
Tara de origine: CH;  
GTIN: 4044918611411;  
Customs tariff number: 85369010000;  
Pret: 2,45 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-terminal-block-suitable-for-ex-i-applications-without-push-buttons-with-snap-in-mounting-foot-for-plate-thickness-0-6-1-2-mm-fixing-hole-3-5-mm-oe-2-5-mm2-cage-clamp-2-50-mm2-blue-142859>