



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 2.5 MM²; SUITABLE FOR EX
E II APPLICATIONS; SIDE AND CENTER MARKING; FOR DIN-15 RAIL; CAGE
CLAMP®; 2,50 MM²; LIGHT GRAY**

Ratings per: IEC/EN 60947-7-1;
Current nominal: 22; A
Nominal voltage EN (Ex e II): 440; V
Connection technology: CAGE CLAMP®;
Operating tool:
Connectable conductor materials: Copper;
Solid conductor: 0.08 ... 2.5 mm² / 28 ... 12 AWG;
Fine-stranded conductor: 0.08 ... 4 mm² / 28 ... 12 AWG;
Strip length: 6 ... 7 mm / 0.24 ... 0.28 inch;
Total number of connections: 2;
Total number of potentials: 1;
Number of levels: 1;
Wiring type: Front-entry wiring;
Width: 5 mm / 0.197 inch;
Height from upper-edge of DIN-rail: 26.5 mm / 1.043 inch;
Depth: 34.5 mm / 1.358 inch;
Design: horizontal;
Mounting: DIN-15 rail;
Marking level: Side marking;
Color: light gray;
Insulating material: Polyamide 66 (PA 66);
Fire load: 0,069; MJ
Weight: 3,9; g
Product Group: 16 (Rail Mounted Terminal Block with CCC);
Packaging: BOX;

Tara de origine: DE;
GTIN: 4044918852395;
Customs tariff number: 85369010000;
Pret: 4,84 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-through-terminal-block-2-5-mm2-suitable-for-ex-e-ii-applications-side-and-center-marking-for-din-15-rail-cage-clamp-2-50-mm2-light-gray-142905>