



WAGO 3-CONDUCTOR ACTUATOR SUPPLY TERMINAL BLOCK; WITH GROUND CONTACT; WITH COLORED CONDUCTOR ENTRIES; 2.5 MM²; CAGE CLAMP®; 2,50 MM²; GRAY

Tensiune nominala (III/3): 125; V

Curent nominal: 5; A

Tensiune nominala (III/3) 2: 250; V

Curent nominal 2: 6,3; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tehnologie conexiune: CAGE CLAMP®;

Tip actionare: Operating tool;

Connectable conductor materials: Copper; Aluminum;

Solid conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Fine-stranded conductor: 0,08 ... 2,5 mm² / 28 ... 12 AWG;

Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;

Numar total de conexiuni: 4;

Total number of potentials: 4;

Numar nivele: 4;

Wiring type: Front-entry wiring;

Note (conductor cross-section): 12 AWG: THHN, THWN;

Latime: 5 mm / 0.197 inch;

Inaltime from upper-edge of DIN-rail: 63,5 mm / 2.5 inch;

Adancime: 90,5 mm / 3.563 inch;

Design: angled;

Tip montaj: DIN-35 rail;

Marking level: Center marking;

Culoare: gray;

Material izolator: Polyamide 66 (PA 66);

Fire load: 0,232; MJ

Greutate: 17,5; g
Product Group: 1 (Rail Mounted Terminal Blocks);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4045454093761;
Customs tariff number: 85369010000;
Pret: 40,79 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/3-conductor-actuator-supply-terminal-block-with-ground-contact-with-colored-conductor-entries-2-5-mm2-cage-clamp-2-50-mm2-gray-143012>