



WAGO T-DISTRIBUTION CONNECTOR; 3-POLE; COD. A; 1 INPUT; 2 OUTPUTS; 3 LOCKING LEVERS; FOR FLYING LEADS; WHITE

Note on Contact Resistance: approx. 1 m Ω of contact resistance approx. 0.25 m Ω contact transition plug/socket;

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 250; V

Tensiune nominala de supratensiune (III/3): 4; kV

Curent nominal: 25; A

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala UL 1977: 600; V

Curent nominal UL 1977: 23; A

Numar poli: 3;

Total number of potentials: 3;

Ground function: with preceding ground contact;

Distanta intre pini: 10 mm / 0.394 inch;

Latime: 34 mm / 1.339 inch;

Inaltime: 36,1 mm / 1.421 inch;

Adancime: 48,9 mm / 1.925 inch;

Coding: A;

Mating force of a plug-in connection: approx. 20 ... 70 N (depending on pole number);

Retention force of a plug-in connection: When locked: > 80 N;

Unmating force of a plug-in connection: when unlocked: approx. 20 ... 70 N (depending on pole number);

Number of mating cycles: ?200, without resistive load 100, with resistive load $I_N = 25$ A, tested (4 mm²/AWG 12);

Distributor type: T-distribution connector;

Marking: L ? N;

Protection type: IP20;

Note on protection type: Only when mated (these compact connectors are not designed for use in open, easily

accessible areas).;

Potential marking: L ? N;

Application: General mains applications;

Suitable: for flying leads;

Tip contact (pluggable connector): Socket/plug;

Mismatching protection: Yes;

Locking of plug-in connection: locking lever;

Locking lever: yes;

Culoare: white;

Material izolator: Polyamide 66 (PA 66);

Contact material: Copper or copper alloy (surface-treated);

Fire load: 0,33; MJ

Greutate: 16,5; g

Processing temperature: -5 ... +40 °C;

Continuous operating temperature: -35 ... +85 °C;

Note on continuous operating temperature: Insulating parts for temperatures ? 105 °C;

Tip ambalare: BOX;

Tara de origine: DE;

GTIN: 4044918582117;

Customs tariff number: 85366990990;

Pret: 22,45 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/t-distribution-connector-3-pole-cod-a-1-input-2-outputs-3-locking-levers-for-flying-leads-white-143108>