



**WAGO 2-CONDUCTOR CENTER TERMINAL BLOCK; SUITABLE FOR EX E II APPLICATIONS; WITHOUT PUSH-BUTTONS; 2.5 MM<sup>2</sup>; CAGE CLAMP®; 2,50 MM<sup>2</sup>; LIGHT GRAY**

Tensiune nominala EN (Ex e II): 690; V  
Curent nominal (Ex e II): 23; A  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 2,5 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Note (conductor cross-section): 12 AWG: THHN, THWN;  
Latime: 6 mm / 0.236 inch;  
Inaltime de la fata: 22.1 mm / 0.87 inch;  
Adancime: 32 mm / 1.26 inch;  
Design: horizontal;  
Tip montaj: Mounting flange;  
Marking level: Center marking;  
Culoare: light gray;  
Fire load: 0,073; MJ  
Greutate: 3,8; g  
Product Group: 9 (Std. Chassis Mt. Blocks);  
Tip ambalare: BOX;  
Tara de origine: CH;

GTIN: 4044918415071;

Customs tariff number: 85369010000;

Pret: 4,42 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-center-terminal-block-suitable-for-ex-e-ii-applications-without-push-buttons-2-5-mm2-cage-clamp-2-50-mm2-light-gray-143124>