



### **WAGO CONDUCTOR SUPPORT, BASE; 7-POLE; 2,50 MM<sup>2</sup>; WHITE**

Ratings per: IEC/EN 60664-1;  
Tensiune nominala (III/2): 500; V  
Tensiune nominala de supratensiune (III/2): 4; kV  
Curent nominal: 6; A  
Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;  
Certificari: UL 1059;  
Tehnologie conexiune: IDC;  
Numar tipuri de conexiuni: 1;  
Numar nivele: 1;  
Latime: 40 mm / 1.575 inch;  
Inaltime de la fata: 21.5 mm / 0.846 inch;  
Adancime: 42 mm / 1.654 inch;  
Culoare: white;  
Material group: I;  
Material izolator: Polyamide 66 (PA 66);  
Flammability class per UL94: V0;  
Clamping spring material: Chrome nickel spring steel (CrNi);  
Contact material: Cupru electrolitic(ECu);  
Contact plating: tin-plated;  
Fire load: 0,138; MJ  
Greutate: 4,9; g  
Temperature stability: 105; °C  
Product Group: 8 (Misc. Chassis Mount Blocks);  
Tip ambalare: bag;  
Tara de origine: CN;  
GTIN: 4050821830290;  
Customs tariff number: 39269097900;

Pret: 1,61 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/conductor-support-base-7-pole-2-50-mm2-white-143147>