



**WAGO 2-CONDUCTOR THROUGH TERMINAL BLOCK; 6 MM²; WITH TEST OPTION;
SAME PROFILE AS 2-CONDUCTOR DISCONNECT TERMINAL BLOCK; SIDE AND
CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; PUSH-IN CAGE CLAMP®;
6,00 MM²; GRAY**

Voltage type 1: AC/DC;

Voltage type 2: DC;

Ratings per: IEC/EN 60947-7-1;

Tensiune nominala (III/3): 1000; V

Tensiune nominala de supratensiune (III/3): 12; kV

Curent nominal: 30; A

Tensiune nominala (III/3) 2: 1500; V

Tensiune nominala de supratensiune (III/3) 2: 12; kV

Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;

Tensiune nominala CSA (Use Group B): 600; V

Curent nominal CSA (Use Group B): 30; A

Tensiune nominala CSA (Use Group C): 1000; V

Curent nominal CSA (Use Group C): 30; A

Tehnologie conexiune: Push-in CAGE CLAMP®;

Tip actionare: Push-in; Open Tool Slot;

Connectable conductor materials: Copper;

Nominal cross-section: 6 mm²;

Solid conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Solid conductor; push-in termination: 2,5 ... 10 mm² / 14 ... 8 AWG;

Fine-stranded conductor: 0,5 ... 10 mm² / 20 ... 8 AWG;

Fine-stranded conductor; with insulated ferrule: 2,5 ... 6 mm² / 16 ... 10 AWG;

Fine-stranded conductor; with ferrule; push-in termination: 2,5 ... 6 mm² / 16 ... 10 AWG;

Strip length: 13 ... 15 mm / 0.51 ... 0.59 inch;

Numar total de conexiuni: 2;
Total number of potentials: 1;
Numar nivele: 1;
Wiring type: Front-entry wiring;
Note (conductor cross-section): Depending on the conductor characteristic, a conductor with a smaller cross-section can also be inserted via push-in termination.;
Number of jumper slots: 2;
Latime: 15 mm / 0.591 inch;
Inaltime from upper-edge of DIN-rail: 33 mm / 1.299 inch;
Adancime: 106,9 mm / 4.209 inch;
Design: horizontal type;
Tip montaj: DIN-35 rail;
Marking level: Center/side marking;
Culoare: gray;
Material izolator: Polyamide 66 (PA 66);
Fire load: 0,666; MJ
Greutate: 31,2; g
Product Group: 22 (TOPJOB S);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4050821372486;
Customs tariff number: 85369010000;
Pret: 29,56 LEI (TVA inclus)

Detalii online: <https://www.materialelectrice.ro/2-conductor-through-terminal-block-6-mm2-with-test-option-same-profile-as-2-conductor-disconnect-terminal-block-side-and-center-marking-for-din-rail-35-x-15-and-35-x-7-5-push-in-cage-clamp-6-00-mm2-gray-143169>