



**WAGO 2-CONDUCTOR POWER DISTRIBUTION DISCONNECT TERMINAL BLOCK; 4  
MM<sup>2</sup>; CAGE CLAMP®; 4,00 MM<sup>2</sup>; GRAY**

Tensiune nominala (III/3): 400; V  
Tensiune nominala de supratensiune (III/3): 6; kV  
Curent nominal: 32; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Open Tool Slot;  
Connectable conductor materials: Copper; Aluminum;  
Solid conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Fine-stranded conductor: 0,08 ... 4 mm<sup>2</sup> / 28 ... 12 AWG;  
Strip length: 9 ... 10 mm / 0.35 ... 0.39 inch;  
Numar total de conexiuni: 2;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 6 mm / 0.236 inch;  
Inaltime from upper-edge of DIN-rail: 43,5 mm / 1.713 inch;  
Adancime: 77 mm / 3.031 inch;  
Design: angled;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: gray;  
Greutate: 17,9; g  
Product Group: 17 (TOP JOB installation terminal blocks);  
Tip ambalare: BOX;  
Tara de origine: PL;  
GTIN: 4044918808101;

Customs tariff number: 85365080900;  
Pret: 17,62 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/2-conductor-power-distribution-disconnect-terminal-block-4-mm2-cage-clamp-4-00-mm2-gray-143181>