



**WAGO THT MALE HEADER; 1.0 X 1.0 MM SOLDER PIN; ANGLED; 100%
PROTECTED AGAINST MISMATING; PIN SPACING 3.5 MM; 16-POLE; LIGHT GRAY**

Ratings per: IEC/EN 60664-1;

Tensiune nominala (III/3): 160; V

Tensiune nominala de supratensiune (III/3): 2,5; kV

Tensiune nominala (III/2): 160; V

Tensiune nominala de supratensiune (III/2): 2,5; kV

Tensiune nominala (II/2): 320; V

Tensiune nominala de supratensiune (II/2): 2,5; kV

Curent nominal: 10; A

Legend (ratings): (III / 2) ? Overvoltage category III / Pollution degree 2;

Tensiune nominala UL (Use Group B): 300; V

Curent nominal UL (Use Group B): 10; A

Tensiune nominala UL (Use Group D): 300; V

Curent nominal UL (Use Group D): 10; A

Certificari: UL 1059;

Tensiune nominala CSA (Use Group B): 300; V

Curent nominal CSA (Use Group B): 10; A

Tensiune nominala CSA (Use Group D): 300; V

Curent nominal CSA (Use Group D): 10; A

Numar poli: 16;

Total number of potentials: 16;

Numar tipuri de conexiuni: 1;

Numar nivele: 1;

Distanta intre pini: 3,5 mm / 0.138 inch;

Latime: 58,4 mm / 2.299 inch;

Inaltime: 12,3 mm / 0.484 inch;

Inaltime de la fata: 8,5 mm / 0.335 inch;

Adancime: 10,3 mm / 0.406 inch;
Lungimea pinului de contact: 3,8; mm
Solder pin dimensions: 1 x 1 mm;
Diametrul de gaurire cu toleranta: 1,4 (+0,1) mm;
Tip contact (pluggable connector): Conector tata/fisa;
Connector (connection type): for PCB;
Mismating protection: Yes;
Mating direction to the PCB: 0; °
PCB contact: THT;
Solder pin arrangement: over the entire male connector (in-line);
Number of solder pins per potential: 1;
Culoare: light gray;
Material group: I;
Material izolator: Polyamide 66 (PA 66);
Flammability class per UL94: V0;
Contact material: Cupru electrolitic(ECu);
Contact plating: tin-plated;
Fire load: 0,06; MJ
Greutate: 4,1; g
Temperatura lucru: -60 ... +100 °C;
Product Group: 3 (Multi Conn. System);
Tip ambalare: BOX;
Tara de origine: DE;
GTIN: 4044918872447;
Customs tariff number: 85366990990;
Pret: 21,02 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/tht-male-header-1-0-x-1-0-mm-solder-pin-angled-100-protected-against-mismating-pin-spacing-3-5-mm-16-pole-light-gray-143527>