



**WAGO 3-CONDUCTOR THROUGH TERMINAL BLOCK; 1.5 MM<sup>2</sup>; CENTER MARKING; FOR DIN-RAIL 35 X 15 AND 35 X 7.5; CAGE CLAMP®; 1,50 MM<sup>2</sup>; RED**

Ratings per: IEC/EN 60947-7-1;  
Tensiune nominala (III/3): 800; V  
Tensiune nominala de supratensiune (III/3): 8; kV  
Curent nominal: 18; A  
Legend (ratings): (III / 3) ? Overvoltage category III / Pollution degree 3;  
Tehnologie conexiune: CAGE CLAMP®;  
Tip actionare: Operating tool;  
Connectable conductor materials: Copper;  
Solid conductor: 0,08 ... 1,5 mm<sup>2</sup> / 28 ... 16 AWG;  
Fine-stranded conductor: 0,08 ... 1,5 mm<sup>2</sup> / 28 ... 16 AWG;  
Strip length: 8 ... 9 mm / 0.31 ... 0.35 inch;  
Numar total de conexiuni: 3;  
Total number of potentials: 1;  
Numar nivele: 1;  
Wiring type: Front-entry wiring;  
Latime: 4 mm / 0.157 inch;  
Inaltime from upper-edge of DIN-rail: 27 mm / 1.063 inch;  
Adancime: 62,5 mm / 2.461 inch;  
Design: horizontal type;  
Tip montaj: DIN-35 rail;  
Marking level: Center marking;  
Culoare: red;  
Material izolator: Polyamide 66 (PA 66);  
Fire load: 0,104; MJ  
Greutate: 5,4; g  
Tip ambalare: BOX;

Tara de origine: DE;  
GTIN: 4044918650502;  
Customs tariff number: 85369010000;  
Pret: 5,91 LEI (TVA inclus)

Detalii online: <https://www.materialeelectrice.ro/3-conductor-through-terminal-block-1-5-mm2-center-marking-for-din-rail-35-x-15-and-35-x-7-5-cage-clamp-1-50-mm2-red-143752>